

ESWPLUS IP68 Waterproof Weighing Scale











OIML

FEATURES

✓ IP68 CERTIFIED BY SGS

✓ EU-TYPE EXAMINATION CERTIFICATE: Number T10896(LCD models only)

- Sealed waterproof silica gel strip blocks water from infiltrating into the scale.
- Surrounded by waterproof grade sheeting to ensure the water free.
- 1/3,000~1/6,000 display resolution available.
- LCD or LED display selectable.
- Stainless steel made for anti-rust.
- High speed of 24bits AD fast reacts and shortens the weighing operation duration.
- Selectable units: Kilogram (kg), gram (g), ounce (oz), and pound (lb) weighing units available.
- Built-in rechargeable battery can be easily replaced.
- Low power indication and auto power off.
- Well-designed protection point for transportation.
- Concave handle for easy carrying.

IP68



SPECIFICATION

| MODEL | CAPACITY | DIVISION | RESOLUTION |
|------------------------------|----------|----------|------------|
| ESW Plus-3 ESW-E Plus-3 | 3kg | 0.5g | 1/6,000 |
| | | 1g | 1/3,000 |
| ESW Plus-6 ESW-E Plus-6 | 6kg | 1g | 1/6,000 |
| | | 2g | 1/3,000 |
| ESW Plus-15 ESW-E Plus-15 | 15kg | 2g | 1/7,500 |
| | | 5g | 1/3,000 |
| ESW Plus-30 ESW-E Plus-30 | 30Kg | 5g · | 1/6,000 |
| | | 10g | 1/3,000 |

120mm

Operating Temperature: $-10^{\circ}\text{C} \sim 40^{\circ}\text{C} (14^{\circ}\text{F} \sim 104^{\circ}\text{F})$

LCD Display: 35x108mm; 6 digits, 25mm (height), LED backlight

LED Display: 35x108mm; 6 digits, 15mm (height)

Power Source: AC 100V~240V (±10%) adapter+DC 6V / 4Ah rechargeable battery

Dimensions: 240 x 120 x 280mm (W x H x D)

Weight of the scale: Approximately 3.5 kg