



WAVE





















- IP 56 wash down design
- Digital calibration
- Double over-load protection
- · Full range tare; Auto zero tracking
- Low power indication and auto power off
- Easily adjusted leveling feet for stability of the scale
- Curve-form base for easy carrying and handling
- Smooth surface and easy-to-disassemble platter for convenient maintenance
- Stainless steel platter
- Dry batteries model also available

WAVE (LCD, 5 keys): Kilogram (kg), gram (g), ounce (oz), and pound (lb) weighing unit available

Options:

- WAVE: OIML approval model available for 1/3000 display resolution
- Second display



Specifications:

1/6000 resolution model also available for non-approval model

MODEL	CAPACITY	DIVISION
WAVE-1.5	1.5 kg (3 lb)	0.5 g (0.001 lb)
. WAVE-3	3 kg (6 lb)	1 g (0.002 lb)
WAVE-6	6 kg (12 lb)	2 g (0.005 lb)
WAVE-15	15 kg (30 lb)	5 g (0.01 lb)
WAVE-30	30 kg (60 lb)	10 g (0.02 lb)

 $\textbf{Operating Temperature: -5°C \sim 40°C (23°F \sim 104°F); Approval model: -10°C \sim 40°C (14°F \sim 104°F)}$

Power Source: DC 10V/1A Adaptor + DC 6V/5AH Rechargeable Battery or 6 x R14 1.5V dry batteries (not included)

Dimensions: $300 \times 140 \times 250 \text{ mm}$ (W x H x D)

Platter Size: 225 x 195mm (W x D)

Display: LCD, 6 digits, height 25 mm